

# 1. PRODUCT & COMAPNY IDENTIFICATION

**SUPPLIER DETAILS:** 

Sprayroq 2870 Crestwood Blvd Irondale, AL 35210 (205)957-0020 Sprayroq.com

EMERGENCY: CHEMTREC 800.424.9300

# 2. HAZARD(S) IDENTIFICATION

# **CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:**

# GHS LASSIFICATION IN ACCORDANCE WITH 29 CFR 1910 (OSHA HCS):

HEALTH	Acute toxicity, 5 Oral
HEALTH	Skin corrosion/irritation, 2
HEALTH	Serious eye damage/eye irritation, 2 A
HEALTH	Respiratory or skin sensitization, 1 Respiratory
HEALTH	Respiratory or skin sensitization, 1 Skin
HEALTH	Carcinogenicity, 2
HEALTH	Specific target organ toxicity - Single exposure, 3

### **GHS LABEL ELEMENTS**

SIGNAL WORD

**PICTOGRAM** 

DANGER



# GHS HAZARD STATEMENTS

H303	May be harmful if swallowed
H315	Causes skin irritation
H319	Causes serious eye irritation
H334	May cause allergy or asthma symptoms of breathing difficulties if inhaled
H317	May cause an allergic skin reaction
H351	Suspected of causing cancer
H336	May cause drowsiness or dizziness

## **GHS PRECAUTIONARY STATEMENTS**

P260	Do not breathe dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves/protective clothing/eye protection/face protection
P284	Wear respiratory protection.
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove con tact lenses if
	present and easy to do. Continue rinsing
P310	Immediately call a POISON CENTER or doctor/physician



## HAZARDS NOT OTHERWISE CLASSIFIED (HNOC) OR NOT COVERED BY GHS

#### ROUTE OF ENTRY:

Eyes; Ingestion; Inhalation; Skin

### TARGET ORGANS:

Respiratory system; Skin; Eyes

### INHALATION:

At room temperature, MDI vapors are minimal due to low vapor pressure. However, heating, spraying, foaming, or otherwise mechanically dispersing (drumming, venting or pumping) operations may generate vapor or aerosol concentrations sufficient to cause irritation or other adverse effects. Excessive exposure may cause irritation of the eyes, upper respiratory tract and lungs. Severe overexposure may lead to bronchitis, bronchial spasm and pulmonary edema. May cause respiratory sensitization with asthma-like symptoms in susceptible individuals. MDI concentrations below the exposure guidelines may cause allergic respiratory reactions in individuals already sensitized. Symptoms may include coughing, dryness of throat, headache, nausea, difficult breathing and a feeling of tightness in the chest. Effects may be delayed. Impaired lung function (decreased ventilator capacity) has been associated with overexposure to isocyanates.

**Chronic:** As a result of previous repeated overexposures or a single large dose, certain individuals develop isocyanate sensitization (chemical asthma) or tissue injury in the upper respiratory tract. Animal tests indicate skin contact alone may also lead to allergic respiratory reaction. These effects may be permanent. Any person developing asthmatic reaction or other sensitization should be removed from further exposure

### SKIN CONTACT:

Causes irritation with symptoms of reddening, itching, swelling, rash, scaling or blistering. Prolonged or repeated exposure can cause skin irritation, reddening, dermatitis, and in some individuals, sensitization. Skin contact may result in allergic skin reactions or respiratory sensitization, but is not expected to result in absorption of amounts sufficient to cause other adverse effects. May stain skin. Cured material is difficult to remove.

## EYE CONTACT:

As a liquid, vapor, aerosol or dust, may cause irritation, inflammation, and/or damage to sensitive eye tissue. Symptoms include reddening, tearing, stinging and swelling. May cause corneal injury. Prolonged contact may cause conjunctivitis.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

## **INGREDIENTS:**

CAS#	%	CHEMICAL NAME
101-68-8	30-60%	4,4'-Methylenediphenyl diisocyanate
0	40-60%	MDI Prepolymer, trade secret



# 4. FIRST AID MEASURES

#### INHALATION:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility immediately.

#### SKIN CONTACT:

Wash off in flowing warm water or shower with soap. Remove and wash contaminated clothing and discard contaminated shoes. For severe exposure, get under safety shower after removing clothing, then seek medical attention. If redness, itching or a burning sensation develops or persists after the area is washed, consult a physician.

### **EYE CONTACT:**

Flush with large amounts of water for 15 minutes. Materials containing MDI may react with the moisture in the eye forming a thick material that is difficult to remove. Get immediate medical attention.

#### **INGESTION:**

DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious person. Seek medical attention.

# **5. FIRE FIGHTING MEASURES**

FLAMMABILITY:	OSHA - none; DOT - none
FLASH POINT:	>300°F
BURNING RATE:	N/A
AUTOIGNITION TEMP:	NDA
LEL:	N/A
UEL:	N/A

Use dry chemical, foam, carbon dioxide, water spray for large fires. The reaction between water and hot isocyanate may be vigorous. If possible, contain fire run-off water.

### PROTECTIVE EQUIPMENT:

Wear positive-pressure self-contained breathing apparatus with full face mask and full protective clothing.

#### **UNUSUAL HAZARDS:**

At temperatures greater than 400°F, polymeric MDI can polymerize and decompose which will cause pressure build-up in closed containers. Explosive rupture is possible. Use cold water to cool fire-exposed containers. Water contamination will produce carbon dioxide. Do not reseal contaminated containers as pressure buildup may rupture the containers. Downwind personnel must be evacuated.

#### FIRE DEGRADATION PRODUCTS:

Isocyanate vapor and mist, carbon dioxide, carbon monoxide, nitrogen oxides and traces of hydrogen cyanide.



# **6. ACCIDENTAL RELEASE MEASURES**

#### SPILL:

Evacuate and isolate spill area. Remove any ignition sources. With adequate ventilation and appropriate personal protective equipment, cover the area with an inert absorbent material such as clay or vermiculite and transfer to metal waste containers. Move container to a well ventilated area (outside), but do not seal the container with the isocyanate mixture. Larger quantities of liquid may be transferred directly to drums for disposal. Decontaminate or discard all clean-up equipment. Contain large spills to prevent entry into water systems.

NOTE: ISOCYANATES WILL REACT WITH WATER AND GENERATE CARBON DIOXIDE. THIS COULD RESULT IN THE RUPTURE OF ANY CLOSED CONTAINERS.

#### **CLEAN UP:**

The area should then be flushed with a decontamination solution. The decontamination solution is a 5-10% mixture of sodium carbonate and 0.5% liquid detergent in water solution or a 3-8% concentrated ammonium hydroxide and 0.5% liquid detergent in water. Use 10 parts decontamination solution to 1 part spilled material. If the ammonium hydroxide solution is used, ammonia will be evolved as a vapor. Use caution to avoid exposure to high concentrations of ammonia. Allow to stand for 48 hours letting evolved carbon dioxide escape.

# 7. HANDLING & STORAGE

#### HANDLING PRECAUTIONS:

Use personal protective equipment when transferring material to or from drums, totes or other containers. Use only in areas of adequate ventilation. The reaction of polyols and isocyanates generates heat. Contact of the reacting materials with skin or eyes can cause irritiation and may be difficult to remove from the affected areas. Do not smoke or use naked lights, open flames, space heaters, or other ignition sources near pouring, frothing or spraying operations.

### SPECIAL EMPHASIS FOR SPRAY APPLICATIONS:

Inspect the application area from the potential to expose other persons or for overspray to drift onto buildings, vehicles or other property. When spraying building exteriors, persons entering or exiting the building as well as those inside could be exposed to polyisocyanates due to wind conditions, open windows or air intakes. Do not begin application work until these potential problems have been corrected.

#### STORAGE REOUIREMENTS:

When stored between 15° and 30°C (60° and 85°F) in dry place in tightly sealed containers, typical shelf life is 6 months or more from the date of manufacture. Consult technical data sheet for shelf life requirements affecting performance quality. Should freezing occur, the material must be thawed thoroughly and mixed until uniform. Opened containers must be handled properly to prevent moisture pickup. Do not reseal if moisture contamination is suspected.



# 8. EXPOSURE CONTROL/PERSONAL PROTECTION

#### **ENGINEERING CONTROLS:**

MDI has a low vapor pressure at room temperature. Monitoring is required to determine engineering controls. Uses requiring heating and/or spraying may require more agressive engineering controls or PPE. Eyewash and safety showers should be available.

### PERSONAL PROTECTIVE EQUIPMENT:

HMIS PP, K | Full Face Respirator, Gloves, Full Suit, Boots

Respiratory Protection: Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand Protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

**Eye Protection:** Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

**Skin & Body Protection:** Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

**Hygiene Measures:** Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Respiratory Protection: Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand Protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

**Eye Protection:** Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

**Skin & Body Protection:** Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

**Hygiene Measures:** Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

# Sprayroq Safety Data Sheet sprayshield green 2 part a

### COMPONENTS WITH WORKPLACE CONTROL PARAMETERS:

TWA	0.0050 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Respiratory sensitization	
C	0.02 ppm	USA. OSHA - TABLE Z-1 Limits for Air Contaminants
	0.2 mg/m3	1910.1000
C	0.02 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z- 1
	0.2 mg/m3	Limits for Air Contaminants
*The \	value in mg/m3 is approximate. Ce	eiling limit is to be determined from breathing-zone air samples.

TWA	0.0050 ppm 0.05 mg/m3 10 minute ceiling value	USA. NIOSH Recommended Exposure Limits
	TO HILLIAGE CELLING VALUE	
C	0.2 ppm	USA. NIOSH Recommended Exposure Limits
	0.2 mg/m3	
	10 minute ceiling value	

# 9. PHYSICAL & CHEMICAL PROPERTIES

Appearance	Non-pigmented liquid
Physical State	Liquid
Odor Threshold	No data available
Spec Grav./Density	N/A
Viscosity	No data available
Boiling Point	Not determined
Flammability	None
Partition Coefficient	No data available
Vapor Pressure	No data available
рН	No data available
Evap. Rate	<1
Decomp Temp	No data available

Odor	Weakly aromatic
Molecular Formula	N/A
Solubility	Not soluble in water
Percent Volatile	0%
Freezing/Melting Pt.	58°F to 68°F
Flash Point	>300°F
Vapor Density	>1
Ignition Temp	NDA
UFL/LFL	No data available

# **10. STABILITY & REACTIVITY**

### CHEMICAL STABILITY:

Polyisocyanates are highly reactive chemicals that should be handled and stored in a way to avoid many common substances, including water and moisture. Product is stable under normal conditions.

# CONDITIONS TO AVOID:

Moisture and/or water. Keep from freezing. Keep away from oxiding agents and open flame. Avoid sparks, flame and temperature above 400°F.



# Sprayroq Safety Data Sheet sprayshield green 2 part a

#### MATERIALS TO AVOID:

Water; alkalis; ammonia; alcohols; amines; acids and metal compounds.

### HAZARDOUS DECOMPOSITION:

By fire or excessive heat: carbon monoxide, carbon dioxide, oxides of nitrogen, traces of hydrogen cyanide, ammonia and MDI vapors. Excess gas may rupture containers.

#### HAZARDOUS POLYMERIZATION:

May occur with incompatible reactants, water or temperatures over 400°F.

# 11. TOXICOLOGICAL INFORMATION

# 4,4'-METHYLENEDIPHENYL DIISOCYANATE (101-68-8) [30-60%]

# Information on toxicological effects:

### **ACUTE TOXICITY:**

ORAL LD50 LD50 ORAL - RAT:	4,700 mg/kg
INHALATION LC50 DERMAL LD50:	No data available

# Other information on acute toxicity

# SKIN CORROSION/IRRITATION: SERIOUS EYE DAMAGE/EYE IRRITATION:

EYES - RABBIT:	Moderate eye irritation
RESPIRATORY OR SKIN SENSITIZATION:	No data available
May cause allergic respiratory and skin reactions	3

#### GERM CELL MUTAGENICITY:

Laboratory experiments have shown mutagenic effects

GENOTOXICITY IN VITRO - HUMAN:	Lymphocyte sister chromatid exchange
GENOTOXICITY IN VIVO - RAT:	Inhalation DNA damage

#### **CARCINOGENICITY:**

This product is or contains a component that is not classifiable as to its carcinogenicity based on its IARC, ACGIH, NTP, or EPA classification. Limited evidence of carcinogenicity in animal studies.

IARC: 3 - GROUP 3:	Not classifiable as to its carcinogenicity to humans (Diphenylmeth ane-4,4- diisocyanate)
ACGIH:	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH
NTP:	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP
OSHA:	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.



# Sprayroq Safety Data Sheet sprayshield green 2 part a

REPRODUCTIVE TOXICITY - RAT - INHALATION:

MATERNAL EFFECTS: Other effects

SPECIFIC DEVELOPMENTAL ABNORMALITIES:

MUSCULOSKELETAL SYSTEM: No data available

TERATOGENICITY: No data available

SPECIFIC TARGET ORGAN TOXICITY:

SINGLE EXPOSURE (GLOBALLY HARMONIZED SYSTEM): May cause respiratory irritation

REPEATED EXPOSURE (GLOBALLY HARMONIZED SYSTEM): No data available

**ASPIRATION HAZARD:** 

ASPIRATION HAZARD: No data available

### POTENTIAL HEALTH EFFECTS:

May be fatal if inhaled. Causes respiratory tract irritation. May be harmful if swallowed. May be harmful if absorbed through skin. Causes skin irritation. Causes eye irritation.

### SIGNS AND SYMPTOMS OF EXPOSURE:

Cough, shortness of breath, headache, nausea, vomiting, pulmonary edema. Effects may be delayed.

SYNERGISTIC EFFECTS: No data available

# **Additional information**

RTECS: NO9350000

MDI and polymeric MDI are not listed by NTP, IARC or regulated by OSHA as carcinogens.

Lung tumors have been observed in laboratory animals exposed to aerosol droplets of MDI/polymeric MDI (6mg/m3) for their lifetime. Tumors occured concurrently with respiratory irritation and lung injury. Concurrent exposure guidelines are expected to protect against these effects.

Other chemicals in this product that are listed by NTP, IARC or regulated by OSHA as carcinogens: None

# 12. ECOLOGICAL INFORMATION

# 4,4'-METHYLENEDIPHENYL DIISOCYANATE (101-68-8) [30-60%]

# Information on ecological effects:

## TOXICITY:

DAPHNIA EC50 - DAPHNIA MAGNA (WATER

FLEA) AND OTHER AQUATIC INVERTEBRATES:	0.35 mg/l - 24 h
PERSISTENCE AND DEGRADABILITY:	No data available
BIOACCUMULATIVE POTENTIAL:	No data available
MOBILITY IN SOIL:	No data available
PBT AND VPVB ASSESSMENT:	No data available
OTHER ADVERSE EFFECTS:	Do not empty into drains



# 13. DISPOSAL CONSIDERATIONS

## **DISPOSAL:**

Any disposal practice must be in compliance with all federal, state and local laws and regulations. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this MSDS incomplete, inaccurate or otherwise inappropriate. Waste characterization and disposal compliance are the responsibility solely of the party generating the waste or deciding to discard or dispose of the material.

Do not allow material to enter sewers, a body of water, or contact the ground. Refer to RCRA 40 CFR 261, and/or any other appropriate federal, state or local requirements for proper classification information.

# 14. TRANSPORT INFORMATION

Non DOT/RCRA regulated

# 15. REGULATORY INFORMATION

# COMPONENT (CAS#) [%] - CODES:

RQ(5000LBS), 4,4'-Methylenediphenyl diisocyanate (101-68-8) [30-60%] CERCLA, HAP, IARC, MASS, NJHS, OSHAWAC, PA, SARA313, TSCA, TXAIR

## **REGULATORY CODE DESCRIPTIONS:**

RQ:	Reportable Quantity
CERCLA:	Superfund clean up substance
HAP:	Hazardous Air Pollutants
IARC:	IARC Carcinogen Risks
MASS:	MA Massachusetts Hazardous Substances List
NJHS:	NJ Right-to-Know Hazardous Substances
OSHAWAC:	OSHA Workplace Air Contaminants
PA:	PA Right-To-Know List of Hazardous Substances
SARA313:	SARA 313 Title III Toxic Chemicals
TSCA:	Toxic Substances Control Act
TXAIR:	TX Air Contaminants with Health Effects Screening Level



# **16. OTHER INFORMATION**

NFPA:	Health = 2, Fire = 1, Reactivity = 1, Specific Hazard = None
HMIS III:	Health = 2, Fire = 1, Physical Hazard = 1
HMIS PPE:	K - Full Face Respirator, Gloves, Full Suit, Boots





#### **DISCLAIMER:**

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).